

# WAGO *SPEEDWAY 767*

Modular IP67 I/O System



**WAGO**®  
INNOVATIVE CONNECTIONS



Where previously discrete wiring was once required, fieldbuses now provide communication between control unit, system and machine. Depending on equipment type, cabinet-free automation systems help minimize costs for planning, start-up, and servicing. To continue leading the way, WAGO has accelerated its modular *SPEEDWAY 767* I/O-SYSTEM, boosting the performance of IP67-rated components.

## **WAGO *SPEEDWAY 767***

### Modular IP67 I/O System

In addition to requiring a high degree of protection, a robust design and standardized connection technology, there is an increasing demand for highly functional IP67 features that were once only reserved for IP20 systems, such as:

- High-Speed Data Exchange
- Programmable
- Parameterizable
- Diagnostic capable
- Updatable

Typically, machines and systems must be tailored to suit individual requirements while meeting tight customer deadlines. Customer requirements can be incorporated easily and rapidly and then the system can be designed and installed. This makes modular IP67 systems ideal, as they are easily scalable and expandable. These systems allow machines to be first mounted in the factory, tested and then accepted by the customers. Then, they are dismantled, re-installed on customer's site and put into operation.

**WAGO *SPEEDWAY 767*  
offers all of these features.**

# System Features



## Modular Design

- Application-oriented signal acquisition/output

Page 6



## High-Performance Data Transfer

- Fast data exchange

Page 8



## Programmable via CoDeSys 3

- Integrated signal preprocessing

Page 9



## Wide Variety of Parameterization Options

- Fieldbus dependent/independent

Page 10



## Servicing Convenience

- Update-capable, parameter-saving and flexible

Page 11



## Fieldbus Independence

- Meets specific market/system requirements

Page 12



## Asynchronous and Synchronous Diagnostics

- Fast and precise error analysis

Page 13



### **Efficient Power Supply Solution**

- Convenient module supply

**Page 14**



### **Temperature Range of $-25^{\circ}\text{C}$ to $+60^{\circ}\text{C}$**

- Ideal for extreme environments

**Page 16**



### **Excellent Protection**

- EMC, water and dust protection

**Page 18**



### **Screw and DIN-Rail Mount Options**

- Flexible module assembly

**Page 20**



### **Ergonomic Design**

- User-friendly modules design

**Page 22**



### **Topology Example**

- ETHERNET system incl. accessories

**Page 24**



### **Modules Overview**

- *SPEEDWAY* components



**Page 26**

# Modular Design

## Application-Oriented Signal Acquisition/Output


Up to:

- 64 I/O modules per station
- 8 channels per module
- 520 channels per station
- 165ft/50m between two modules
- 1,650ft/500m total extension per station



WAGO SPEEDWAY 767 is a modular IP67 I/O system. SPEEDWAY connects to a fieldbus and on to higher-level control systems via a (programmable) fieldbus coupler. The fieldbus coupler features digital inputs. An integrated system bus interface allows connection to other I/O modules (e.g., analog, digital). This permits signals to be received and transmitted directly in the field. When used in areas of high signal concentration, the modules can be installed in an ex-

tremely compact manner. The I/O modules are connected to each other via data line (system bus) and supply line, allowing multiple power supplies to be used (e.g., when higher power demand is required or greater distances must be bridged). Depending on the fieldbus type, configuration, programming, servicing and diagnostics can be performed via integrated USB port and fieldbus interface.





# High-Performance Data Transfer

## Fast Data Exchange

- Up to 512 digital signals, approx. 700 $\mu$ s
- Up to 256 digital signals + 64 analog signals, approx. 700 $\mu$ s
- Up to 32 digital signals + 8 analog signals, approx. 400 $\mu$ s

Increasing degrees of system automation and the trend toward fast ETHERNET-based controllers or fieldbus protocols call for a high communication bandwidth. Large data volumes are forwarded in short cycles for signal acquisition and transmission within the I/O system.


WAGO SPEEDWAY 767 is designed for this purpose, also offering high synchrony, low jitter/skew and low latency for optimal control of dynamic system processes.



# Programmable via CoDeSys 3

## Integrated Signal Preprocessing

- Object-oriented programming to IEC 61131-3
- One application easily manages different control systems
- Direct cross-communication between control systems



Automation configurations are continuously decentralized and modularized. The WAGO SPEEDWAY 767 PLCs (programmable to IEC 61131-3) were engineered to these standards. These programmable units optimize the system's dynamic response. By preprocessing signals on site, the signal volume for the higher-level controller is

minimized. This enables devices to maintain autonomous operation, as well as independent start-up and operation. Moreover, decentralized intelligence can ensure that device downtime does not lead to a loss of the entire process – system availability is retained.

# Wide Variety of Parameterization Options

## Fieldbus Dependent/Independent

- Extraordinarily high degree of module parameterization
- Fieldbus-independent parameterization via GSD, GSDML and EDS files
- Fieldbus-independent, advanced parameterization via FDT/DTM technology
- Online diagnostics and simulation

All *SPEEDWAY* components can be extensively parameterized. This allows the user to cover a wide range of functions with only a few base modules, as well as flexible system adaptations. Except for only a few modules, parameter setting is performed channel-by-channel. This greatly reduces the number of modules and versions required, minimizing supply and inventory costs.

Depending on the fieldbus used, parameter setting is performed via device description files (e.g., GSD, GSDML, EDS). DTM device drivers based on FDT technology are also provided. These files can be loaded via FDT frame application and allow parameterization of systems having no device description files, as well as extended parameter setting. Access is performed either via USB interface or fieldbus (e.g., ETHERNET).

Examples:

**Digital Input Module:** filter, inversion, simulation, diagnostics

**Digital Output Module:** inversion, substitute value strategy, manual mode, simulation, diagnostics


**Digital Input/Output Module:** operating mode, filter, inversion, substitute value strategy, manual mode, simulation, diagnostics

**Analog Input Module U/I:** voltage/current measuring range, threshold values, filter, simulation, diagnostics

**Analog Input Module RTD:** RTD measuring range, connection type, threshold values, integration time, linearization, simulation, diagnostics

**Analog Input Module TC:** Thermocouple measuring range, threshold values, integration time, linearization, simulation, diagnostics

**Analog Output Module U/I:** voltage/current measuring range, substitute value strategy, manual mode, simulation, diagnostics





- Updatable
- System parameter handling
- “Options handling” for 

### Updatable

Acquisition and operating costs of a system are steadily increasing. This is why your return on investment is now more important than ever. The *SPEEDWAY 767* System is updatable, providing a valuable contribution to cost optimization.

Both coupler and I/O module firmware can be easily updated. This allows quick access to new functionalities, while errors can be fixed without replacing components.

### System parameter handling

All parameterizable *SPEEDWAY* modules feature factory default settings. The modules can be customized to suit-specific systems requirements. *SPEEDWAY* provides the freedom of system parameter handling – not every control system permits direct data parameterization, administration and archiving.

This way, parameter settings won't be lost in case of a module exchange. System parameter handling provides archiving of all settings and checks (e.g., when exchanging

an I/O module) if the right replacement module is used. In the event of a failure, parameter data can be restored quickly and reliably. Optionally, current hardware, software and firmware versions can be checked.

### “Options handling”

Operation-related, variable I/O station configurations of a system (e.g., tool replacement in processing center) can often only be customized with extensive engineering before a changed production process can start. *With PROFIBUS, SPEEDWAY 767 supports variable system configuration without engineering modification.*

Supporting this, the higher-level control system defines various expansion stages within a maximum engineering configuration. This allows the control system to identify a *SPEEDWAY* station modification (number and type of modules) and run a sub-program without engineering modification.

# Fieldbus Independence

Meeting Specific Market/System Requirements

**CANopen**

**PROFI**  
INDUSTRIAL ETHERNET  
**NET**


**DeviceNet**

**PROFI**  
INDUSTRIAL ETHERNET  
**BUS**

**sercos**

**MODBUS/TCP**

**EtherNet/IP**



In order to fulfill specific market and system requirements, *SPEEDWAY 767* supports the fieldbuses shown. For addressing hardware and setting model-specific operation modes, the fieldbus coupler features a display panel. A protective cover safeguards contents from environmental influences and unintended contact.

An USB interface (COM) provides direct system access for programming, parameter-setting and servicing.





- LED and software supported
- Module-by-module and channel-by-channel
- Parameterizable

## Asynchronous and Synchronous Diagnostics

### Fast and Precise Error Analysis


One of the greatest challenges for manufacturers of automation devices is making and keeping the engineering manageable. This is especially important for troubleshooting.

For the IP67 systems, the diagnostic capability is especially significant due to the widespread distribution of a system. Thus, all WAGO SPEEDWAY 767 devices deliver diagnostic data.

A distinction should always be made between module- and channel-specific error messages. The quantity and type of diagnostic information is increasingly being determined by intelligent modules – this facilitates in-depth error analysis. However, this also inevitably leads to an increase in diagnostic data.

The transfer of this data must occur with virtually no delay and without influencing the cycle time. Asynchronous and synchronous transfer mechanisms are therefore supported to meet these challenges, minimizing downtime.

#### Example: LED diagnostics of analog input module



**SB LED:**  
Module status indication during communication (e.g., operation state, error)

**F LED:**  
Indication of channel-wide errors (e.g., short circuit of sensor supply)


**Ch/Er LED:**  
Channel-related status indication (e.g., operation state) and error (e.g., measuring range underflow or overflow, overload)

**Power LED:**  
Logic, sensor and actuator supply indication

# Efficient Power Supply Solution

## Convenient Module Supply

- M12 supply connections
- 18 AWG/0.75mm<sup>2</sup> cable cross-section
- -25%...+30% voltage fluctuation range
- Individual and group power supply
- Separate actuator supply up to 8A
- Electrically isolated power supplies





Select *SPEEDWAY 767* Modules are equipped with M12 connections for supplying energy to modules over great distances. Compared with M8 connections, they offer a connection cross-section of 18 AWG/0.75mm<sup>2</sup> instead of 22 AWG /0.34mm<sup>2</sup>. The related lower line resistance causes a lower voltage drop on the line. In connection with the larger voltage fluctuation range integrated in the modules, greater distances can be bridged between power supply unit and *SPEEDWAY 767*.


An M12 connection contains two lines (logic and sensor supply, as well as actuator supply).

A second supply connection allows for supply groups, or an additional supply for higher power requirements when using 2A output modules. Electrical separations in the modules' power supplies guarantee smooth operation of the system in the event of an error (e.g., short circuit of the actuators).

Inspection and diagnosis of the supply is performed along the entire cable run.

Temperature Range of  $-25^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$

Ideal for Extreme Environments



Even in sub-zero temperatures, WAGO SPEEDWAY 767 will perform reliably. Despite the temperature, additional signal jumpering via passive distributors and sensor/actuator boxes in connection with active IP20 I/O systems is unnecessary. Harsh environmental conditions can be met and additional applications realized. This reduces costs associated with additional materials, assembly and operation.

+60

+60°C



-25

-25 °C

-25 °C



+60 °C

°C

°C





## Excellent Protection

EMC, Water and Dust Protection





- IP67 degree of protection, fully encapsulated
- Inner-metallized housings
- Integrated shield plates



## Uncompromising protection, even in the harshest environments

All modules offer IP67-grade protection and robust construction. Fully encapsulated modules safeguard system operation, even when subjected to temperature extremes and prolonged periods of vibration. The electronic circuit is thus protected long-term.




## Protection both inside and outside

Electromagnetic compatibility – the ability of an electrical component to operate in its intended environment without causing or being influenced by electromagnetic interference – is a central feature of the WAGO SPEEDWAY 767 system.

Electromagnetic shielding made of both metallized housing and shield plate guarantees trouble-free operation within the housing. The interferences are deflected directly on the machine via the mounting rail of the modules or system.

The resulting SPEEDWAY 767 Modules keep with WAGO's philosophy of exceeding standard requirements.



- Carrier rail adapter
- Profile adapter
- CNOMO standard compliance

## Screw and DIN-Rail Mount Options

### Flexible Module Assembly



The modules can be directly screwed onto the machine. Extensive engineering ensures compliance with standardized specifications from the CNOMO guidelines. Because passive distribution boxes and sensor/actuator boxes are also accounted for, WAGO *SPEEDWAY 767* eases the transition from passive to active automation and supports the development of mixed systems through standardized assembly dimensions. DIN and CNOMO adaptors for *SPEEDWAY* housing are available for flexible mounting options.

# Ergonomic Design

## User-Friendly Module Design



- Clear arrangement of connectors, LEDs and marking areas
- Exclusive use of standard M8/M12 connectors
- Detailed text and symbol identification
- Marking strips or WMB markers for customer marking
- Optimum cable layout/LED arrangement
- Clear serial number identification
- Compact design





WAGO SPEEDWAY 767 does not require specialty cables and connectors. Standardized M8 (3 poles) and M12 (4 to 5 poles) connections simplify both assembly and procurement.


Connecting the fieldbus, system bus, power supply and sensors/actuators is performed via coded M12 connectors. This avoids errors in cable connection.

In addition, the device connections are manufactured from metal. Compared to plastic versions, this prevents liquid intrusion that could occur from metal cable connectors being inadvertently cross threaded.



Ergonomics played an important role in the development of WAGO SPEEDWAY 767. The result is a lightweight, compact design that can be used in the most compact areas of machines. Clearly visible printing, labeling and status LEDs provide quick access to module information.



# Topology Example (ETHERNET System incl. Accessories)





## WAGO SPEEDWAY 767



756-1204/..., ETHERNET Cable

756-1306/..., System Bus Cable

# DWAY



# IP67

# Modules Overview

## SPEEDWAY Components

Identification	Description	Item No.
<b>Fieldbus Couplers (FC)</b>		
FC PROFIBUS DP, 8 DI, 24VDC	PROFIBUS-DP/V1 Coupler, incl. 8 digital inputs	767-1101
FC PROFINET IO, 8 DI, 24VDC	PROFINET IO Coupler, incl. 8 digital inputs	767-1201
FC ETHERNET, 8 DI, 24VDC	ETHERNET Coupler, incl. 8 digital inputs	767-1301
FC Sercos, 8 DI, 24VDC	Sercos Coupler, incl. 8 digital inputs	767-1311
FC DeviceNet, 8 DI, 24VDC	DeviceNet Coupler, incl. 8 digital inputs	767-1401
FC CANopen, 8 DI, 24VDC	CANopen Coupler, incl. 8 digital inputs	767-1501
<b>PLCs or Programmable Fieldbus Couplers (PFC)</b>		
PFC ETHERNET, 8 DI, 24VDC	Programmable ETHERNET Coupler, incl. 8 digital inputs	767-2301
PFC CANopen, 8 DI, 24VDC	Programmable CANopen Coupler, incl. 8 digital inputs	767-2501
<b>Digital Input Modules (DI)</b>		
8 DI, 24VDC (8 x M8)	8 digital inputs	767-3801
8 DI, 24VDC (4 x M12)	8 digital inputs	767-3802
8 DI, 24VDC (8 x M8)	8 digital inputs, low-side switching	767-3803
8 DI, 24VDC (4 x M12)	8 digital inputs, low-side switching	767-3804
8 DI, 24VDC (8 x M12)	8 digital inputs	767-3805
<b>Digital Output Modules (DO) .../0000-0800 Interference-Free Version</b>		
8 DO, 24VDC, 0.5A (8 x M8)	8 digital outputs, 0.5A	767-4801 767-4801/0000-0800
8 DO, 24VDC, 0.5A (4 x M12)	8 digital outputs, 0.5A	767-4802 767-4802/0000-0800
8 DO, 24VDC, 2.0A (8 x M8)	8 digital outputs, 2.0A	767-4803 767-4803/0000-0800
8 DO, 24VDC, 2.0A (4 x M12)	8 digital outputs, 2.0A	767-4804 767-4804/0000-0800

Identification	Description	Item No.
<b>Digital Output Modules (DO)</b> .../0000-0800 Interference-Free Version		
8 DO, 24VDC, 0.5A (8 x M8)	8 digital outputs, 0.5A, low-side switching	767-4805
8 DO, 24VDC, 0.5A (4 x M12)	8 digital outputs, 0.5A, low-side switching	767-4806
8 DO, 24VDC, 0.5A (8 x M12)	8 digital outputs, 0.5A	767-4807 767-4807/0000-0800
<b>Specialty Modules</b> .../0000-0800 Interference-Free Version		
Serial Interface RS-232, RS-422/ -485 (4 x M12)	2 serial interfaces + 4 digital inputs/outputs	767-5203
8 DIO, 24VDC, 0.5A (8 x M8)	8 digital inputs/outputs, 0.5A	767-5801 767-5801/0000-0800
8 DIO, 24VDC, 0.5A (4 x M12)	8 digital inputs/outputs, 0.5A	767-5802 767-5802/0000-0800
8 DIO, 24VDC, 0.5A (8 x M12)	8 digital inputs/outputs, 0.5A	767-5803 767-5803/0000-0800
8 DI, 24VDC, HS (4 x 12)	8 digital inputs, <10 $\mu$ s delay	767-3801
8 DO, 24VDC, HS (4 x M12)	8 digital outputs, 0.1A, <1 $\mu$ s delay	767-4808
4 DIO, 24VDC, 0.2A HS (4 x M12)	4 digital inputs/outputs, 0.2A, <10 $\mu$ s/<1 $\mu$ s delay	767-5401
<b>Analog Input Modules (AI)</b>		
4 AI U/I	4 analog inputs, voltage/current (0-20mA, 0-22mA, 4-20mA, $\pm$ 20mA, 0-10V, $\pm$ 10V)	767-6401
4 AI RTD	4 analog inputs, RTD (Pt100/200/500/1000, Ni100/120/1000 Resistance: 1k $\Omega$ /2k $\Omega$ , Potentiometer adjustment: 0-100%)	767-6402
4 AI TC	4 analog inputs, thermocouple (type: B/C/E/J/K/N/R/S/T, voltage: $\pm$ 36/ $\pm$ 72/ $\pm$ 145/ $\pm$ 290mV)	767-6403
<b>Analog Output Modules (AO)</b>		
4 AO U/I	4 analog outputs, voltage/current (0-20mA, 4-20mA, $\pm$ 20mA, 0-10V, $\pm$ 10V)	767-7401
<b>Supply Modules</b>		
Power Divider (1 x M23 + 6 x M12)	Power divider	767-9101

## WAGO Service Worldwide

### Germany

WAGO Kontakttechnik  
Minden  
Tel. ++49/571/887/0  
Fax ++49/571/887/169

### Austria

WAGO Kontakttechnik  
Wien  
Tel. ++43/1/615/07/80  
Fax ++43/1/615/07/75

### Belgium

WAGO Kontakttechnik  
Zaventem  
Tel. ++32/2/7/17/90/90  
Fax ++32/2/7/17/90/99

### China

WAGO ELECTRONIC Co. Ltd.  
Tianjin  
Tel ++86/22/59617688  
Fax ++86/22/59617668

### England

WAGO, Ltd.  
Rugby  
Tel. ++44/1788/568008  
Fax ++44/1788/568050

### France

WAGO CONTACT S.A.  
Paris  
Tel. ++33/148172590  
Fax ++33/148632520

### Italy

WAGO ELETTRONICA SRL  
Casalecchio di Reno (BO)  
Tel. ++39/051/6132112  
Fax ++39/051/6272174

### Japan

WAGO Co. of JAPAN Ltd.  
Tokyo  
Tel. ++81/3/5627/2050  
Fax ++81/3/5627/2055

### Poland

WAGO ELWAG sp. z o. o.  
Wroclaw  
Tel. ++48/71/3604670/78  
Fax ++48/71/3604699

### Singapore

WAGO Electronic Pte. Ltd.  
Singapore  
Tel. ++65/62866776  
Fax ++65/62842425

### Switzerland

WAGO CONTACT SA  
Domdidier  
Tel. ++41/26/676/75/86  
Fax ++65/26/676/75/01

### Mexico

WAGO Corporation  
Queretaro  
Tel. 001/800/309/5975  
+ 52/442/221/5946  
Fax + 52/442/221/5063

### Canada

WAGO Corporation  
Tel. 800/DIN Rail (346-7245)  
Fax 262/255-3232  
www.wago.ca

WAGO Corporation  
N120 W19129 Freistadt Road  
Germantown, Wisconsin 53022  
800 / DIN Rail (346-7245)  
Fax 262 / 255-3232  
info.us@wago.com  
www.wago.us

